



VERIGE ŠKORPIO d.o.o. PREDDVOR; SLOVENIJA

**FORESTRY ROLLING GUIDING SHOE WITH CHAIN BLOCK 30° / 90°**



30°

90°

Code	Dim. and Grade	Weight A [kg]	Wire rope Ømax	Max. allowed. loading [kg]	Break. load [KN]
75103	D6-7 K10/12	1,13	14	4200	84
75102	D7 K10/14	1,15	14	4200	84
75101	D7-8 K10/48	1,35	14	5500	110
75100	D10K10/18	2,30	18	8250	165
75094	D6-7 K10/12	1,13	14	4200	84
74402	D7 K10/14	1,15	14	4200	84
74403	D7-8 K10/48	1,35	14	5500	110
74404	D10K10/18	2,30	18	8250	165

**FORESTRY ROLLING GUIDING SHOE AND ROLLING CHAIN BLOCK ONE LINK 30° / 90°**



30°

90°

Code	Dim. and Grade	Weight A[kg]	Wire rope Ømax	Max. allowed. loading [kg]	Break. load [KN]
80327	d 6-7 k10/12	1,18	14 mm	4200	84
80326	D7 k10/14	1,20	14 mm	4200	84
80325	d7-8 K10/14	1,4	14 mm	5500	110
80324	D10 K10/14	2,5	18 mm	8250	165
80331	d 6-7 k10/12	1,18	14 mm	4200	84
80330	D7 k10/14	1,20	14 mm	4200	84
80329	d7-8 K10/14	1,4	14 mm	5500	110
80328	D10 K10/14	2,5	18 mm	8250	165

**FORESTRY ROLLING GUIDING SHOE AND ROLLING CHAIN BLOCK DOUBLE LINK 30° / 90°**



30°

90°

Code	Dim. and Grade	Weight A[kg]	Wire rope Ømax	Max. allowed. loading [kg]	Break. load [KN]
80335	d 6-7 k10/12	1,2	14 mm	4200	84
80334	D7 k10/14	2,22	14 mm	4200	84
80333	d7-8 K10/14	1,45	14 mm	5500	110
80332	D10 K10/14	2,6	18 mm	8250	165
80339	d 6-7 k10/12	1,2	14 mm	4200	84
80338	D7 k10/14	2,22	14 mm	4200	84
80337	d7-8 K10/14	1,45	14 mm	5500	110
80336	D10 K10/14	2,6	18 mm	8250	165



VERIGE ŠKORPIO d.o.o. PREDDVOR; SLOVENIJA

**FORESTRY ROLLING GUIDING SHOE WITH ROLLING CHAIN BLOCK 30° / 90°**



30°

90°

Code	Dim. and Grade	Weight A[kg]	Wire rope Ø max	Max. allowed. loading [kg]	Break. load [KN]
80343	D6-7K10/14	1,06	14 mm	4200	84
80342	D7 K10/14	1,10	14 mm	4200	84
80341	D7-8K10/14	1,40	14 mm	5500	110
80340	D10K10/18	2,5	18 mm	8250	165
80347	D6-7K10/14	1,06	14 mm	4200	84
80346	D7 K10/14	1,10	14 mm	4200	84
80345	D7-8K10/14	1,40	14 mm	5500	110
80344	D10-K10/18	2,5	18 mm	8250	165

**FORESTRY ROLLING GUIDING SHOE WITH ROLLING CHAIN BLOCK ONE LINK 30° / 90°**



30°

90°

Code	Dim. and Grade	Weight A[kg]	Wire rope Ø max	Max. allowed. loading [kg]	Break. load [KN]
80351	D6-7K10/14	1,11	14 mm	4200	84
80350	D7 K10/14	1,14	14 mm	4200	84
80349	D7-8K10/14	1,45	14 mm	5500	110
80348	D10K10/18	2,6	18 mm	8250	165
80355	D6-7K10/14	1,11	14 mm	4200	84
80354	D7 K10/14	1,14	14 mm	4200	84
80353	D7-8K10/14	1,45	14 mm	5500	110
80352	D10K10/18	2,6	18 mm	8250	165